

# Speaker/Zip Cables

## DUPLEX SPEAKER WIRE



**DESCRIPTION:**

- Stranded copper conductors 22, 18, or 16 AWG
- PVC insulation
- CL2

**SPECIFICATIONS:**

NEC 725 UL13 **RoHS**

**APPLICATION:**

Burglar alarm, audio control systems, limited circuits.

**STANDARD LENGTH**

Standard lengths of 1000 ft, 500 ft, 250 ft reels or boxes.

Product Code	Number of Conductors/ Gauge	Jacket Thickness	External Dimensions Inches	Net Weight Lb/kft
720553	22	0.02"	0.132 x 0.070"	9
*720559	22	0.02"	0.132 x 0.070"	9
720583	18	0.022"	0.169 x 0.089"	17
720600	16	0.024"	0.201 x 0.110"	28

\* Non UL-approved

Conductor Gauge AWG	Conductor Construction Wire/AWG	Conductor Resistance D.C. Maximum $\Omega$ /kft @ 20°C		Voltage Rating
		Bare Copper	Tinned Copper	
22	7/30	16.30	17.10	300 V
18	19/30	6.55	6.90	300 V
16	26/30	4.00	4.20	300 V

\*All values are nominal, and subject to manufacturing tolerances.